



POWER RELAY

Safety Approval

UL US NO. E164730

CQC NO. CQC09002030014


NO. 50097843

Features

- Low profile, height 15.7mm
Dimension: 29.0×12.6×15.7(mm)
- Switching capacity 16A
- Contact: 1 Form A, 1 Form C
- Sensitivity 400mW
- Insulation: 5KV
Creepage:10mm



ORDERING INFORMATION



SPECIFICATION

CONTACT DATA

Contact Form	1 Form A, 1 Form C	
Contact Material	Ag Alloy	
Contact Rating	Resistive: 16A 250VAC/30VDC Inductive: 8A 250VAC Cosφ=0.4	
Contact Resistance	Max. 100mΩ (6VDC 1A)	
Load	Max. Switching Voltage	380VAC/30VDC
	Max. Switching Current	16A
	Max. Switching Power	4,000VA, 240W
	Min. Switching Load	5VDC, 100mA
Life	Electrical	100,000 operations
		50,000 operations (Resistive: Cosφ=0.4, L/R=7ms)
	Mechanical	20,000,000 operations

GENERAL DATA

Insulation Resistance		Min. 1000MΩ 500VDC
Dielectric Strength	Between open contacts	1,000VAC, 1min
	Between coil and contacts	5,000VAC, 1min
Operate Time	Max. 10ms	
Release Time	Max. 5ms	
Operating Temperature	-40°C to +85°C	
Humidity	35~95%RH, +40°C	
Shock Resistance	Endurance	1,000m/s ²
	Misoperation	100m/s ²
Vibration Resistance	Endurance	10~55Hz, 1.5mm double amplitude
	Misoperation	10~55Hz, 1.5mm double amplitude
Weight	Approximately 13.00g	

Note:Data shown are of initial value

COIL DATA

Nominal Coil Power	400mW
--------------------	-------

SAFETY APPROVAL

File Number	Contact Form	Power Consumption	Coil Voltage	Contact Rating	Remark
UL E164730	A	0.4W	5 - 48VDC	20A 250VAC	Ambient Temperature: 85°C
	A/C	0.4W	5 - 48VDC	16A 250VAC	Class F insulation Ambient Temperature: 85°C
TUV 50097843	A/C	0.4W	5 - 48VDC	16A 250VAC	Ambient Temperature: 85°C
CQC09002030014 (GB/T 21711.1-2008)	A/C	0.4W	5 - 48VDC	16A 250VAC	Ambient Temperature: 85°C

Specifications subject to change without notice

ISO9001、ISO/TS16949、ISO14001 Approved

COIL DATA

Ambient Temperature: 23°C



Model	Nominal Voltage VDC	Coil Resistance Ω +/-10%	Operate Voltage \leq VDC	Release Voltage \geq VDC	Coil Power mW
HCP3-S-DC5V	5	62.5	3.5	0.5	400
HCP3-S-DC6V	6	90.0	4.2	0.6	
HCP3-S-DC9V	9	202.5	6.3	0.9	
HCP3-S-DC12V	12	360	8.4	1.2	
HCP3-S-DC24V	24	1440	16.8	2.4	
HCP3-S-DC48V	48	5760	33.6	4.8	

OUTLINE, WIRING DIAGRAM, MOUNTING HOLE LAYOUT (UNIT: mm)


1 Form C

Outline

Mounting Hole Layout (Bottom View)





Wiring Diagram (Bottom View)




1 Form A

Outline

Mounting Hole Layout (Bottom View)




Wiring Diagram (Bottom View)




REFERENCE DATA


Maximum Switching Power



Life Curve



Max. Ambient Temp. Vs. Coil Voltage



- A: Coil temperature = Ambient temperature.
- B: 110% of nominal coil voltage at rated contact load.